



## Organic Anionic Emulsion Solve 161

### Material Safety Data Sheet

Date Issued: 08/23/08

Date Revised: 08/23/08

#### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: **SOLVE 161**  
CHEMICAL FAMILY: Anionic polyacrylamide  
Molecular Formula: Mixture  
COMPANY: **WaterSolve, LLC, 4964 Starr St. SE, Grand Rapids, MI 49546, USA**  
For Product information call **616-575-8693**.  
EMERGENCY PHONE: For emergency involving spill, leak, fire, exposure or accident call  
CHEMTREC: 1-800-424-9300. Outside the USA and Canada call 703-527-3887.

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

OSHA Regulated Components				
Component	CAS NO.	%	OSHA (pel)	AGGIH (TLV)
Petroleum distillate	064742-47-8	22.0-	500 ppm 1200mg/m3	(skin)
Hydrotreated light		25.0	165ppm (Supplier)	

#### 3. HAZARDS IDENTIFICATION

##### Emergency Overview

Appearance and odor: Greenish-white, liquid, petroleum distillate odor  
Statement of Hazard: **WARNING! Causes Skin Irritation and May cause Eye Irritation**

##### Effects of overexposure:

The estimated acute oral (rat) LD50, acute dermal (rabbit) LD50 and 4-hour inhalation (rat) LC50 values for this material are >5000mg/kg, >2000 mg/kg and >20 mg/L respectively. Direct contact with this material may cause moderate skin and mild eye irritation. Over exposure to vapor may cause respiratory tract irritation and central nervous system depression. Refer to Section 11 for toxicology information on the regulated components of this product.

#### 4. FIRST AID MEASURES

##### Ingestion:

If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

##### Skin Contact:

Remove contaminated clothing and shoes without delay. Wash immediately with plenty of water. Do not reuse contaminated clothing without laundering. Get medical attention if pain of irritation persists after washing or if signs and symptoms of overexposure appear.

##### Eye Contact:

Rinse immediately with plenty of water for at least 15 minutes.

Inhalation:

Remove to fresh air. If breathing is difficult, give oxygen. Obtain medical advice if there are persistent symptoms

5. **FIRE FIGHTING MEASURES**

**Suitable Extinguishing Media:**

Use water spray, carbon dioxide or dry chemical.

**Protective Equipment:**

**Firefighters, and others exposed, wear self-contained breathing apparatus. Wear full firefighting protective clothing. See MSDS Section 8 (exposure Controls/Personal Protection)**

**Special Hazards:**

**Keep containers cool by spraying with water if exposed to fire.**

**Mechanical/Static Sensitivity Statements: None**

6. **ACCIDENTAL RELEASE MEASURES**

Personal precautions:

Where exposure level is not known, wear NIOSH approved, positive pressure, self-contained respirator. Where exposure level is known, wear NIOSH approved respirator suitable for level of exposure. In addition to the protective clothing/equipment in Section 8, wear impervious boots.

Methods For Cleaning Up:

Products may cause a slip hazard. Spilled material should be absorbed onto an inert material and scooped up. Flush spill area with water. If slipperiness remains apply more dry-sweeping compound.

7. **HANDLING AND STORAGE**

Handling

Precautionary Measures: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

Special Handling Statements: None

STORAGE

To avoid product degradation and equipment corrosion, do not use iron, copper or aluminum containers or equipment. Flashpoint determinations on materials of this type are required by certain regulations and scientific standards to be performed using a Pensky-Martens type closed cup test method. This method indicates a flash point greater than 93.3C (200F). Although there was no flashpoint detected below 93.3C (200F) by the Pensky-Martens Closed Tester method, some flammable vapors were evolved during the test as evidenced by the enlargement for the test flame; therefore, caution should be exercised during storage and handling.

Storage Temperature: Store at < 32° C 90° F

Reason: Integrity

8. **EXPOSURE CONTROLS/PERSONAL PROTECTION**

Engineering Measures:

Where this material is not used in a closed system, good enclosure and local exhaust ventilation should be provided to control exposure.

Respiratory Protection: Where exposures are below the established exposure limit, no respiratory protection is required. Where exposures exceed the established exposure limit, use respiratory protection recommended for the material and level of exposure.

**Eye Protection:**

Wear eye/face protection such as chemical splash proof goggles or face shield. Eyewash equipment and safety shower should be provided in areas of potential exposure.

**Skin Protection:**

Avoid skin contact. Wear impermeable gloves and suitable protective clothing.

**Additional Advice:**

Food, beverages and tobacco products should not be carried, stored or consumed where this material is in use. Before eating, drinking, or smoking, wash face and hands thoroughly with soap and water.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance and Odor:	grayish white liquid, petroleum distillate odor
Boiling Point:	Similar to water
Melting Point:	<-20°C -4°F (freezing point)
Vapor Pressure:	Not available
Specific Gravity:	1.03 – 1.06
Vapor Density:	Similar to water
% Volatile (By Wt):	56 - 62
pH:	6 – 9.5
Saturation in Air (% by Vol):	Not applicable
Evaporation Rate:	Not available
Solubility in Water:	Limited by viscosity
Volatile Organic Content:	Not available
Flash point:	>100.6°C 213°F closed cup
Flammable Limits (% by vol):	Not available
Autoignition temp:	Not available
Decomposition temp:	Not available
Odor Threshold	Not available
Partition coefficient (n-octanol/water)	Not available

**10. STABILITY AND REACTIVITY**

Stability:	Stable
Conditions to avoid:	None known
Polymerization:	Will not occur
Conditions to Avoid:	None known
Incompatible Materials:	No specific incompatibility
Hazardous Decomposition Products:	Carbon monoxide ammonia Oxides of nitrogen Oxides of sulfur (includes sulfur di and tri oxides) Carbon dioxide

**11. TOXICOLOGICAL INFORMATION**

Toxicological information for the product is found under Section 3.

Toxicological information on the OSHA regulated components of this product is as follows:

Ammonia vapor can cause respiratory tract and eye irritation. Direct contact with ammonia solutions causes irreversible eye damage, mucous membrane swelling and skin burns. The LC50 in rats by

inhalation after 1-hour exposure is 7338 mpp (1.27 mg/L). Single dose oral administration of ammonia solution to rats at 350 mg/kg produced no toxic effects.

Alcohols (c10-16), ethoxylated toxicological properties have not been fully investigated. Based on similar materials, the acute oral (rat) LD50 is estimated to range from 1600-2500 mg/kg and the acute dermal (rabbit) LD50 value is estimated to be >2000mg/kg. Similar materials produced severe eye irritation and moderate skin irritation in studies with rabbits.

Ethoxylated Oley amine toxicological properties have not been fully investigated. It is reported to have an oral (rat) LD50 value of 1500 mg/kg. It is also reported to be severely irritating to eyes and moderately irritating to the skin.

California Proposition 65 Warning (applicable in California only)- This product contains (a) chemical(s) known to the State of California to cause cancer .

## 12. ECOLOGICAL INFORMATION LC50

**This is not classified as dangerous for the environment. The effects on aquatic organisms are due to an external (non-systemic) mode of action, and are significantly reduce (by a factor of 7-20) within 30 minutes due to binding of the product to dissolved organic and inorganic sorbents such as clays and silts. All ecological information provided was conducted on a structurally similar product. Acute toxicity tests conducted on the polymer using environmentally representative water gave the following results:**

Zebra Fish (Brachydanio rerio) 96 hr LC 50 >1-10 mg/l  
Water Flea (Daphnia magna) 48hr EC 50 >10-100 mg/l  
Green Algae (selenastrum capricomutum) 72 hr IC 50 >100 mg/l  
DEGRADATION

Test: CO2 Evolution: Modified Sturm (OECD 301B)

Duration : 28 day

Procedure: Ready biodegradability

The material is not readily biodegradable. The large polymer size is incompatible with transport across biological membranes and diffusion; the bioconcentration factor is therefore considered to be zero.

## 13. DISPOSAL CONSIDERATIONS

The information on RCRA waste classification and disposal methodology provided below applies only to the product, as applied. If the material has been altered or contaminated, or it has exceeded its recommended shelf life, the guidance may be inapplicable. Hazardous waste classification under federal regulations (40 CFR Part 261 et seq) is dependent upon whether a material is a RCRA "listed hazardous waste" or has any of the four RCRA "hazardous waste characteristics." Refer to 40 CFR Part 261.33 to determine if a given material to be disposed of is a RCRA "listed hazardous waste"; information contained in Section 15 of this MSDS is not intended to indicate if the product is a "listed hazardous waste." RCRA Hazardous Waste Characteristic. There are four characteristics defined in 40 CFR Section 261.21-61.24: Ignitability, Corrosivity, Reactivity, and Toxicity. To determine Ignitability, See Section 5 of this MSDS (flash point). For Corrosivity, see sections 9 and 14 (pH and DOT corrosivity). For Reactivity, see Section 10 (incompatible materials). For Toxicity, see Section 2 (composition). Federal regulations, may also apply to the classification of the material to be disposed. WaterSolve encourages the recycle, recovery and reuse of materials classified as RCRA hazardous wastes to be disposed of by thermal treatment or incineration at EPA approved facilities. WaterSolve has provided the foregoing for information only; the person generating the waste is responsible for determining the waste classification and disposal method.

## 14. TRANSPORT INFORMATION

This section provides basic shipping classification information. Refer to appropriate transportation regulations for specific requirements.

#### US DOT

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazard Class: 9

Packing Group: 111

UN/ID Number: UN3082

Transport Label Required: Miscellaneous

Technical Name: (N.O.S.): Contains ammonium acetate

Hazardous Substances:

Component / CAS No.	Reportable Quantity of Product (lbs)
Ammonium acetate	50000

Comments: Hazardous Substances/Reportable Quantities- DOT requirements specific to Hazardous Substances only apply if the quantity in one package equals or exceeds the product reportable quantity.

#### TRANSPORT CANADA

Proper Shipping Name: Not applicable/Not regulated

#### ICAO/IATA

Proper Shipping name: Not applicable/Not regulated

Packing instructions/maximum net quantity per package:

Passenger Aircraft:

Cargo Aircraft:

#### IMO

Proper shipping name: Not applicable/Not regulated

### 15. **REGULATORY INFORMATION**

#### INVENTORY INFORMATION

USA : All components of this product are included on the TSCA Chemical Inventory or are not required to be listed on the TSCA Chemical I inventory.

Canada: All components of this product are included on the Domestic Substances List (DSL) or are not required to be listed on the DSL

European Union (EU): All components of this product are included on the European Inventory of Existing Chemical Substances (EINECS) or are not required to be listed on EINECS.

Australia: All components of this product are included in the Australian Inventory of Chemical Substances(AICA) or have been assessed by Worksafe Australia.

China: All components of this product are NOT included on the Chinese inventory. The Chinese State Environmental Protection Administration (SEPA) has granted a Polymer Exemption for the non-listed substance to WaterSolve, LLC and the product can be imported into China ONLY under specific conditions.

Japan: All components of this product are NOT included on the Japanese (ENCS) inventory.

Korea: All components of this product are NOT included on the Korean (ECL) inventory.

Philippines: All components of this product are NOT included on the Philippine (PICCS) inventory.

**OTHER ENVIRONMENTAL INFORMATION**

The following components of this product may be subject to reporting requirements pursuant to Section 313 of CERCLA (40 CFR 372), Section 12(b) of TSCA, or may be subject to release reporting requirements (40 CFR 307, 40 CFR 311, etc.) See Section 13 for information on waste classification and waste disposal of this product.

<u>COMPONENT</u>	<u>CAS NO.</u>	<u>%</u>	<u>TPQ(lbs)</u>	<u>RQ(lbs)</u>	<u>S313</u>	<u>TSCA 12B</u>		
Ammonium Acetate	631-61-8	2.0-10.0	None	5000	No	No		
<table border="1"> <tr> <td>Product Classification under section 311 of SARA</td> </tr> <tr> <td>Acute (Y)</td> </tr> </table>							Product Classification under section 311 of SARA	Acute (Y)
Product Classification under section 311 of SARA								
Acute (Y)								

**16. OTHER INFORMATION**

NFPA HAZARD RATING (National Fire Protection Association)

Health 2- Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

Fire 1 – Materials that must be preheated before ignition can occur.

Reactivity 0 –Materials that in themselves are normally stable, even under fire exposure conditions.

REASON FOR ISSUE: New Format

This information is for the specific material described only and may not be valid if the material is used in combination with any other materials or in any process. The user is responsible to determine the completeness of the information and suitability for the user's own particular use. The knowledge and belief of the company, the information is accurate and reliable as of the date indicated but the company makes no express or implied warranty of merchantability for the material or the information. The company makes no express or implied warranty of fitness for a purpose for the material or for the information.